

FEATURES/BENEFITS:

- > Improved floor quality
- > Full color soft touch LCD display with integrated diagnosis
- > Somero Floor Levelness System[®] (optional)
- > Column-Block Protection
- > OASIS Laser Control System
- > 360° Machine Rotation with 2-wheel, 4-Wheel and Crab Steering
- > Somero Quick GradeSet System™
- > Hydraulic oil pre-heater
- > Heated seat, hand and foot areas
- > Automatic throttle
- > Automatic soft landing
- > Programmable Quick Pass
- > Compatible with the 3-D Profiler System[®]

SPECIFICATIONS:

WEIGHT	13,600 lbs / 6,169 kg
WIDTH	7' 2" / 2.2 m
HEIGHT	8' 3" / 2.5 m
LENGTH	27' 10" / 8.4 m (transport mode)
ENGINE (STANDARD)	74 HP / 55.0 kW Deutz Turbo Diesel, Tier 4i
ENGINE (OPTIONAL)	65 HP / 48.5 kW Cummins Diesel QSS 2.8, Tier 4 Final
SELF-PROPELLED	Standard
SCREED HEAD WIDTH	12' / 3.7 m (standard)
SCREED HEAD WIDTH	14' / 4.3 m (optional)

OPTIONAL:

- 12' / 3.6 m or 14' / 4.3 m Roller Plow
- Hydraulic Pressure Washer (3,000 PSI / 207 bar)
- Extra Lower-Frame Storage Compartment
- Powered head rotation on the end of the boom
- Tire options
- Spare parts kits

**WHAT OUR CUSTOMERS SAY:**

"The S-22 is so fluid and a lot easier to operate. Machine responds rapidly to every movement with no hesitation. IT'S THE BEST MACHINE I'VE RAN!"

— Jack Mills, *C & C Plumbing Services, Inc., Groveland, FL*